

navigo

12VS

Open FiberglassTenders



	Overal Length	:	12′/ 3.66m	Number of Chambers	:	3 + 1	Shaft Length Option 1: 15"/38.1cm
S	Overal Beam	:	6′/ 1.82m	Person Capacity	:	6	Shaft Length Option 2 : 20" / 50.8cm
ш	Inside Length	:	8´9″/ 2.67m	Weight	:	202lb / 92kg	RDC Design Category : C
S P	Inside Beam	:	2´9″/ 0.84m	Recommended HP	:	20hp / 14.9kw	
	Tube Diameter	:	18″/ 0.46m	Maximum HP	:	30hp / 22.4kw	

Stainless Steal Bow Eye
4 Stainless Steal Davit Lifting Points
Stainless Steal Towing Rings & Tie Downs

Hand	Laid Fiberg	lass Deep	"V" Hull

- stem Laminated into Hull
- Bow Locker/ Seat with Vent

ΩS

പ

ЧЧ

z⊢

 $\triangleleft \triangleleft$

μш

νц

<u>ہ ר</u>

∢ш

ZĽ

0⊃

ΓA

ு ய

Оц

- ----

Raised Single Solid Rub Rail

- Bow Locker/ Seat with Vent Bow Locker Storage to Fit a 6 Gal Portable Fuel Tank (Only for 15" Shaft Version) Diamond Shape Non Skid Deck Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip

Deck Condensation Plug

3 Layer Reinforced Seams Paddle with Aluminum Shaft

- Paddle Holders
- Removable Stern Seat Hand Pump
- Maintenance Kit
- Deck Orain with Plug
 Owner's Manual

 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor

 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 Hidden Channel for Fuel Fittings with SS Starburst

 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 Hidden Channel for Fuel Fittings with SS Starburst

Portable 6 gal Fuel Tank Installed in Bow Locker with Fittings (Only for 15" Shaft Version)

Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

- Bow Hatch Cushion
- Tube Chaps
- **Boat Cover**
- Chock Set
- Bow Step with Fold Down Stainless Steal Cleat
- Lateral Fold Down Stainless Steal Cleat

- Removable Rowing Seat
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steal Helm Unit

